

► Perfect ergonomics

With a head length of 154 mm and a weight of 0.8 kg including 12 V/3.0 Ah rechargeable battery

Perfect process control

With six different screwdriving stages, adjustable according to time, speed, direction and angle of rotation, as well as torque

Maximum service life and robustness

Thanks to the brushless EC motor and high-quality, wear-free components



- ► Compact 2.0 and 3.0 Ah rechargeable battery from the 12 V class
- ▶ The compact design is ideal for 12 V tools
- ▶ Optimised battery capacity makes it suitable for most 12 V applications
- ▶ 6.0 Ah battery with maximum runtime in Bosch's 12 V category
- Extremely high battery capacity delivers up to 300% more runtime than the 12V 2.0 Ah Professional
- ► Compact and with perfect balance between size and capacity for ultimate performance with 12 V power tools
- ► Compatible since 2005: all of our batteries are compatible with new and existing Bosch Professional tools in the same voltage class.



Smaller, shorter, lighter - the cordless industrial screwdriver with perfect ergonomics.

- ► Perfect ergonomics: With a head length of 154 mm and a weight of 0.8 kg including 12 V/3.0 Ah rechargeable battery
- ▶ Perfect process control: With six different screwdriving stages, adjustable according to time, speed, direction and angle of rotation, as well as torque
- ► Maximum service life and robustness: Thanks to the high-quality and wear-free components
- ► Brushless (EC) motor for 30 % more efficiency (compared to conventional DC motors) and extremely long service life
- LED ring light for optimally illuminating the work area, adjustable via a USB port
- ► Precision shut-off clutch with Cmk > 1.67 (in +/-10 % tolerance range according to VDI 2647)
- ► Visual and audible indication of screwdriving results and battery status, for the greatest process reliability
- ► Bosch Premium lithium-ion technology for long lifetime and runtime




Torque, hard/soft as per ISO 5393 (Nm)	Speed (no-load)	Bit holder	Battery specifications (V)	Direction of rotation	Weight as per EPTA (kg)
1.5 – 6	135 – 670 *	1/4" quick- change chuck	12 V/3.0 Ah**	R/L	0.85 kg (including rechargeable battery)
1 - 3	220 – 1100 *	1/4" quick- change chuck	12 V/3.0 Ah**	R/L	0.85 kg (including rechargeable battery)
0.5 – 2	135 - 670 *	1/4" quick- change chuck	12 V/3.0 Ah**	R/L	0.85 kg (including rechargeable battery)
	* Below 50 % speed to power may be lowe		** Rechargeable battery not in the items included		

Smaller, shorter, lighter - the cordless industrial screwdriver with perfect ergonomics.

- ▶ Perfect ergonomics: With a head length of 346 mm and a weight of 1.1 kg including 12 V/3.0 Ah rechargeable battery
- ► LED ring light for optimally illuminating the work area, adjustable via a USB port
- ► New extremely small angle head with ¼" quick-change chuck or 3/8" square, can be continuously rotated
- ► Precision shut-off clutch with Cmk > 1.67 (in +/-10 % tolerance range according to VDI 2647)
- ► Visual and audible indication of screwdriving results and battery status, for the greatest process reliability
- ► Bosch Premium lithium-ion technology for long lifetime and runtime

ANGLE EXACT.	Part number	
ANGLE EXACT 12V-12-400	0 602 496 600	



Configuration	Torque, hard/soft as per ISO 5393 (Nm)	Speed (no-load)	Battery specifications (V)	Direction of rotation	Weight as per EPTA (kg)
with 12V angle head	2-10 maximum 12*	74–370** with a maximum Power Boost of 500	12V 3.0 Ah***	R/L	1.1***
OBS! Levere	ras utan v	inkelhuvud			
with adapter 0 602 496 022 and 180W angle head	2.5-8 maximum 9*	95–480** with a maximum Power Boost of 650	12V 3.0 Ah***	R/L	1.2****
För vinkelhu	vud se sid	dan 5			
with adapter 0 602 496 022 and straight screw head 0 607 453 631	1.5-6 maximum 6.5*	134-670** with a maximum Power Boost of 910	12V 3.0 Ah***	R/L	1.2****
with 12V angle head	2.0-6.0	120–600** with a maximum Power Boost of 800	12V 3.0 Ah***	R/L	1.1****
with adapter 0 602 496 022 and 180W angle head	1.5–4.5	150–780** with a maximum Power Boost of 1040	12V 3.0 Ah***	R/L	1.2***
with adapter 0 602 496 022 and straight screw head 0 607 453 631	1.0-3.0	220–1100** with a maximum Power Boost of 1450	12V 3.0 Ah***	R/L	1.2***
with 12V angle head	1.0-3.5	120–600** with a maximum Power Boost of 800	12V 3.0 Ah***	R/L	1.1****
with adapter 9602 496 022 and 180W angle bad	0.8–2.5	150-780** with a maximum Power Boost of 1040	12V 3.0 Ah***	R/L	1.2***
with adapter 0 602 496 022 and 180W angle lead with adapter 0 602 496 022 and straight screw head 0 607 453 631	630g	220–1100** with a maximum Power Boost of 1450	12V 3.0 Ah***	R/L	1.2***
	* Only possible in cycle operation: < 5 threaded connections per	** limited power at speeds <50%	*** Battery not in the items included		****incl. battery 3.0 Ah and angle head

BATTERY PACKS AND CHARGERS FOR EXACT AND ANGLE EXACT LITHIUM-ION

12 V battery packs and chargers



Lithium-ion		Part number	Description	Voltage (V)	Capacity (Ah)	Weight as per EPTA (kg)
GBA 12 V/2.0 Ah Professional		0 602 494 020	GBA 12V 2.0 Ah rechargeable battery, pack of 27	12	2,0	27 x 0.175
GBA 12 V/3.0 Ah Professional		0 602 496 012	GBA 12V 3.0 Ah rechargeable bat- tery, pack of 28	12	3.0	28 x 0.18
GBA 12 V/6.0 Ah Professional	1	0 602 496 013	GBA 12V 6.0 Ah rechargeable bat- tery, pack of 12	12	6.0	12 x 0.385

Li-lon quick charger	Part number	Description	Voltage (V)	Weight as per EPTA (kg)
GAL 12V-40 Fully charges the GBA 12V/3.0 Ah in 50 minutes and the GBA 12V/6.0 Ah in 95 minutes.	0 602 494 007	GAL 12V-40 charger, pack of 16	230	16 x 0.45
	0 602 496 014	GAL 12V-40 charger, pack of 16 (UK plug)	230	16 x 0.45

18 V lithium-ion battery packs and chargers



Lithium-ion		Part number	Description	Voltage (V)	Capacity (Ah)	Weight as per EPTA (kg)
18 V/2.0 Ah	H	0 602 494 002	Pack of 12 batteries	18	2,0	12 x 0.35
18 V/4.0 Ah		0 602 494 004	Pack of 12 batteries	18	4.0	12 x 0.6
18 V/5.0 Ah	THE PERSON NAMED IN COLUMN TO PERSON NAMED I	0 602 494 003	Pack of 12 batteries	18	5.0	12 x 0.6
ProCORE18V 4.0Ah		0 602 494 034	Pack of 15 batteries	18	4.0	15 x 0.515



Li-lon quick charger	Part number	Description	Voltage (V)	Weight as per EPTA (kg)
GAL 1880 CV Fully charges the GBA 18V/2.0 Ah in 30 minutes and the GBA 18V/5.0 Ah in 45 minutes.	0 602 494 035	GAL 1880 CV charger, pack of 18	230	18 x 0.7
	0 602 494 036	GAL 1880 CV charger, pack of 18 (UK plug)	230	18 x 0.7
GAL 18V-40 Fully charges the GBA 18V/2.0 Ah in 35 minutes and the GBA 18V/5.0 Ah in 70 minutes.	0 602 494 039	GAL 18V-40 charger, pack of 18	230	18 x 0.55
	0 602 494 040	GAL 18V-40 charger, pack of 18 (UK plug)	230	18 x 0.55

BATTERY PACKS AND CHARGERS FOR EXACT AND BT-EXACT


Nickel metal hydride	Part number	Description	Voltage (V)	Capacity (Ah)	Weight as per EPTA (kg)
9.6 V batteries	2607335681	Battery pack	9.6	2.6	0.55
	0602490025	Pack of 10 batteries	9.6	2.6	5.5
12 V batteries	2607335683	Battery pack	12	2.6	0.7
	0602490026	Pack of 10 batteries	12	2.6	7
14.4 V batteries	2607335685	Battery pack	14.4	2.6	0.8
	0602490027	Pack of 10 batteries	14.4	2.6	8

Quick charger		Part number	Voltage (V)	Weight as per EPTA (kg)
AL 2450 DV Multivolt charger. Charges all Bosch NTC battery packs from 7.2–14.4 V with APT shank.	1	2 607 225 027	230	1.0

46 | Accessories | EXACT original accessories | Accessories | 47

ANGLE HEADS FOR EXACT AND ANGLE EXACT

Vinkelhuv	ud för 12V	Part number	Max. torque (Nm)	Drive end	Weight (kg)	Quantity
Angle heads 12V		0 602 496 020	15	3/8" square	0.18	1
	-	0 602 496 021	15	1/4" QRC	0.18	1
Adapter 12V Adapter for ANGLE EXACT 12V for use with		0 602 496 022 0 602 496	022	Flange for 180W angle head	0.1	4
the 180W angle heads	- April ma	För att an	vända de	essa huvuder	n nedan	till 12V mas
Straight head		0 607 453 631	6	1/4"-QRC	0.2	1
Angle head Gear ratio 1.4:1	(F)	0 607 453 617	27	1/4"-square	0.2	1
	-8 -	0 607 453 618	27	1/4"-square internal hex	0.2	1
		0 607 453 620	27	3/8"-square	0.2	1
		0 607 453 630	27	1/4"-QRC	0.2	1
HD angle head Required for ANGLE EXACT 30 (gear ratio of 1.4:1)		0 607 451 618	35	3/8"- square	0.22	1
Protective cap For angle heads	suitable for angle heads 180W 0607453617,618, 620 and630	3 605 500 171	-	-	-	1
	suitable for HD angle head 0607451618	3 605 500 175	-	-	-	1
	suitable for angle head 12V 0602496020 and 021	0602496015				5
Protective cap for large angle head Prevents damage to the workpiece	suitable for ANGLE EXACT ION 30-300, 40- 220, 50-210, 60-120	3 609 202 A29	-	-	-	1



48 | Accessories | EXACT original accessories | Accessories | 49

EXACT 12V AND ANGLE EXACT 12V ACCESSORIES

EXACT 12V and ANGLE EXACT 12V accessories Part number Quantity Covers coloured For quickly identifying the torque range black 0 602 497 008 and with extra large bonding surface blue 0 602 497 004 Suitable for every EXACT 12V and ANGLE EXACT 12V 0 602 497 005 5 red 0 602 497 006 5 green 0 602 497 007 5 yellow **RFID attachment** Black Black cover with NFC chip for wireless (Chip: NXP NTAG screwdriver identification. 0 602 496 011 5 216 – 924 bytes) Suitable for every EXACT 12V and ANGLE EXACT 12V Only available as a pack of 5

EXACT 12V accessories		Part number	Quantity
Protectors Prevent damage to the workpiece Suitable for every EXACT 12V centre grip screwdriver	Clear Fig. example	0 602 496 000	5
	Blue Fig. example	0 602 496 001	5
Will not block motor air vents Only available as a pack of 5	Red Fig. example	0 602 496 002	5
	Green Fig. example	0 602 496 003	5
	Yellow Fig. example	0 602 496 004	5


ANGLE EXACT 12V accessories		Part number	Quantity
Protectors Prevent damage to the workpiece Suitable for every ANGLE EXACT 12V	Clear Fig. example	0 602 496 005	5
angle wrench	Blue Fig. example	0 602 496 006	5
Will not block motor air vents Only available as a pack of 5	Red Fig. example	0 602 496 007	5
	Green Fig. example	0 602 496 008	5
	Yellow Fig. example	0 602 496 009	5

Accessories for battery packs		Part number	Quantity
Battery pack protectors Prevent damage to the battery Only available as a pack of 5	Clear For the GBA 6.0 Ah Fig. example	12V 0 602 496 010	5

EXACT 12V AND ANGLE EXACT 12V ACCESSORIES AND DIMENSIONAL DRAWINGS





EXACT 12V Dimensions in mm





ANGLE EXACT 12V Dimensions in mm





56 | Accessories | EXACT original accessories EXACT original accessories | Accessories | 57